


APPLICABLE STANDARD						
	OPERATING TEMPERATURE RANGE	-40°C TO +80°C(95%RH MAX)	STORAGE TEMPERATURE RANGE	-30°C TO +60°C(95%RH MAX)		
RATING	VOLTAGE	30 V AC	CURRENT	SIGNAL	0.5 A/pin	
				2PINS POWER	1.0 A/pin (ANY OF 2PIN)	
					2.0 A/pin (PIN No.1 and 8)	
APPLICABLE CABLE		Taiyo Cabletec Corporation. E67647-WH AWM 20276 80°C VW-1 Fai 6.8±0.3				
SPECIFICATIONS						
ITEM	TEST METHOD		REQUIREMENTS		QT	AT
CONSTRUCTION						
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		X	X
MARKING	CONFIRMED VISUALLY.		ACCORDING TO DRAWING.		X	X
ELECTRIC CHARACTERISTICS						
CONTACT RESISTANCE	100 mA MAX (DC OR 1000 Hz).		30 mΩ MAX.		X	—
INSULATION RESISTANCE	100 V DC.		500 MΩ MIN.		X	—
VOLTAGE PROOF	250 V AC FOR 1 min.CURRENT LEAKAGE 2mA MAX.		NO FLASHOVER OR BREAKDOWN.		X	—
MECHANICAL CHARACTERISTICS						
INSERTION AND WITHDRAWAL FORCES	A MAXIMUM RATE OF 12.5 mm/min. MEASURED BY APPLICABLE CONNECTOR.		INSERTION FORCE 25 N MAX. WITHDRAWAL FORCE 25 N MAX.		X	—
MECHANICAL OPERATION	5000 TIMES INSERTIONS AND EXTRACTIONS.  MATING SPEED - MANUALLY OPERATED : 200 CYCLES / h		1) CONTACT RESISTANCE: NO INCREASE OF MORE THAN 15 mΩ FROM INITIAL VALUE. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	—
VIBRATION	FREQUENCY 10 TO 500 Hz SINGLE AMPLITUDE 0.75 mm, AT 11 min 10 CYCLES(30 CYCLES IN TOTAL) FOR 3 AXIAL DIRECTIONS.		1) NO ELECTRICAL DISCONTINUITY OF 1μS. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	—
FRETTING CORROSION	490 m/s <sup>2</sup> , 30 TIMES/MIN AT 1000 TIMES.		1) CONTACT RESISTANCE: NO INCREASE OF MORE THAN 60 mΩ FROM INITIAL VALUE. 2) NO ELECTRICAL DISCONTINUITY OF 1μS. 3) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	—
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
	△					
REMARK			APPROVED	RI.TAKAYASU	17.05.10	
			CHECKED	NM.NISHIMATSU	17.05.10	
			DESIGNED	P.EKSOURIYA	17.05.10	
			DRAWN	P.EKSOURIYA	17.05.10	
Unless otherwise specified, refer to IEC 60512.			DRAWING NO.		ELC-129407-00-00	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test						
<b>HRS</b>	SPECIFICATION SHEET		PART NO.	IX40-A-8P-JC(7.1)		
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL251-0015-0-00	△	1/2

SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
SHOCK	490 m/s <sup>2</sup> DURATION OF PULSE 11 ms AT 3 TIMES IN 3 BOTH AXIAL DIRECTIONS.	1) NO ELECTRICAL DISCONTINUITY OF 1μS. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X		—
LOCK STRENGTH	APPLYING 98 N FORCE IN THE MATING AXIS DIRECTION IN STATE IN FITTED WITH APPLICABLE CONNECTOR.	NO UNLOCKING, DAMAGE, CRACK AND LOOSENESS OF PARTS.	X		—
ENVIRONMENTAL CHARACTERISTICS					
THERMAL SHOCK	TEMP -55 → +15 TO +35 → +85 → +15 TO +35 °C TIME 30 → 2 TO 3 → 30 → 2 TO 3 min UNDER 10 CYCLES (MATING APPLICABLE CONNECTOR)	1) CONTACT RESISTANCE: NO INCREASE OF MORE THAN 30 mΩ FROM INITIAL VALUE. 2)INSULATION RESISTANCE: 1 MΩ MIN. (AT DRY) 3) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X		—
HUMIDITY	EXPOSED AT +40 ± 2 °C, HUMIDITY 93 +2 / -3 %, 96h (MATING APPLICABLE CONNECTOR)	1) CONTACT RESISTANCE: NO INCREASE OF MORE THAN 30 mΩ FROM INITIAL VALUE. 2)INSULATION RESISTANCE: 1 MΩ MIN. (AT DRY) 3) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X		—
DRY HEAT	EXPOSED AT +85 ± 2 °C, 1000 h. (MATING APPLICABLE CONNECTOR)	1) CONTACT RESISTANCE: NO INCREASE OF MORE THAN 30 mΩ FROM INITIAL VALUE. 2)INSULATION RESISTANCE: 1 MΩ MIN. (AT DRY) 3) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X		—
COLD	EXPOSED AT -40 ± 3 °C, 1000 h. (MATING APPLICABLE CONNECTOR)	1) CONTACT RESISTANCE: NO INCREASE OF MORE THAN 30 mΩ FROM INITIAL VALUE. 2)INSULATION RESISTANCE: 1 MΩ MIN. (AT DRY) 3) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X		—
CORROSION SALT MIST	EXPOSED AT 5 % SALT WATER, 35 ± 2 °C, 48h. (LEFT UNDER UNMATED CONDITION.)	NO HEAVY CORROSION OF CONTACTS.	X		—
CORROSION So <sub>2</sub> GAS	EXPOSED AT SO <sub>2</sub> 25 ppm, 25 ± 2 °C, 75 ± 5%RH, 96 h. (LEFT UNDER UNMATED CONDITION.)	NO HEAVY CORROSION OF CONTACTS.	X		—
SOLDERBILITY	SOLDERING POINT IMMERSSED IN SOLDER BATH OF 255 ± 5 °C,5 sec. (USING TYPE R FLAX)	SOLDER SHALL COVER MINIMUM OF 95 % OF THE SURFACE BEING IMMERSSED.	X		—
RESISTANCE TO SOLDERING HEAT	TEMPERATURE 350 ± 10 °C,5 sec AT SOLDERING PARTS	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X		—
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC-129407-00-00		
<b>HRS</b>	SPECIFICATION SHEET		PART NO.	IX40-A-8P-JC (7. 1)	
	HIROSE ELECTRIC CO., LTD.		CODE NO	CL251-0015-0-00	 2/2